

Adhesive Primer 484



Adhesive Primer Data Sheet

TECHNICAL DATA SHEET

Adhesive Primer 484 (#120144)

Substrate Pre-Treatment Liquid

ADHESIVE PRIMER 484 is a clear liquid used for the pre-treatment of difficult substrates to improve ink adhesion. This product was originally developed for the pretreatment of polypropylene, but works with most other substrates, including metals. If Adhesive Primer 484 is used flame, plasma, or corona discharge is unnecessary.

USE INSTRUCTIONS: Read Material Safety Data Sheets Prior To Using.

ADHESIVE PRIMER 484 may be applied by spraying, dipping, or brushing. The layer applied should be as thin as possible. If it is applied heavily, the product loses its efficiency. Trans Tech recommends using a soft towel, or felt for the application. Excess solvent can be wiped off immediately from the substrate for an invisible effect. Substrates treated with Adhesive Primer 484 may have ink applied from one minute to two months with acceptable results. Testing is always recommended.

USE & STORAGE CONDITIONS:

Recommended room temperature 70-78 degrees F.

Recommended room humidity 30-50%. For more information see Material Safety Data Sheets.

WARRANTY PERIOD: 2 YEARS FROM SHIP DATE (In original, sealed container)

STORAGE OF PRODUCTS: At room temperatures 35 to 75 Degrees F with low humidity out of direct sunlight.

****Since operating conditions and applications are beyond our control, Trans Tech can not guarantee results, nor assume liability for any problem that may arise. The user should test the suitability of the product for its intended application. No warranty for results obtained, expressed or implied, can be assumed by Trans Tech.**