

Pad Printing Ink

Type B

Ink Data Sheet

NOTE: Read Material Safety Data Sheet (MSDS) Prior To Use

Pad Printing Ink Type B is a two-component product supplied in paste form. Hardener must be added for production use. Ink and hardener should be thoroughly mixed prior to adding thinner. During printing, the ink viscosity may be adjusted with thinner (if needed). A retarder may be added to slow drying rate during printing (normally for high room temperatures or multi-color use). Under most conditions, ink pot life will not exceed eight hours. Recommended room temperature: 70-78 degrees F. Recommended room humidity 30-50 %

ADDITIVES: (See Additives Chart for more listings)

Hardeners: (mixing ratio, ink to additive)

BH HARDENER (Four parts ink to one part hardener; Ratio by weight) For most applications.

BH/N HARDENER (4 : 1 Ratio by weight) More ultraviolet light and abrasion resistant but requires additional drying time.

Thinners: (after adding Hardener)

THINNER B (5 to 20 % by weight) Faster

VD THINNER (5 To 20 % by weight) Medium

THINNER BGA (5 To 20 % by weight) Slower

Retarder: (after adding Hardener and Thinner)

TPD RETARDER (1 To 3 % by weight)

DRYING & CURING: Ink TYPE B dries to the touch within 30 seconds at room temperature. Drying time may be reduced with forced hot air at 200 – 400 degrees F. Normally, full cure is achieved after five to six days depending on curing temperature time; and humidity. Heat curing is necessary for better adhesion and performance results.

USE & STORAGE INFORMATION

(For more detailed information see Material Safety Data Sheet (MSDS) for Type B Ink.

INK TYPE B:

Stir ink thoroughly before removing from container. Reseal lid tightly after using.

Warranty Period: Two years from ship date (In original, sealed container)

HARDENER: Reseal container immediately after using. Hardener is humidity sensitive. As moisture is absorbed, the viscosity first increases, then starts forming crystals. Do not use when crystals first appear.

Warranty Period: one year from ship date (In original, sealed container)

THINNER: Reseal lid tightly after using.

Warranty Period: two years from ship date (In original, sealed container)

RETARDER: Reseal lid tightly after using.

Warranty Period: two years from ship date (In original, sealed container)

STORAGE OF ALL PRODUCTS: At room temperature 60 to 80 Degrees F with low humidity.

Pad Printing Ink

Type B

Ink Data Sheet

AVAILABLE COLORS: (See Color Availability Chart)

Ink Type B is available in:

- 23 Standard Opaque Colors
- Standard Metallic Colors
- Process colors
- Custom Colors Available Upon Request
- C-Mix 2000 Color Matching System

****Since operating conditions and applications are beyond our control, Trans Tech can not guarantee results, nor assume liability for any problem that may arise.**

The user should test the suitability of the product for its intended application. No warranty for results obtained, expressed or implied, can be assumed by Trans Tech.

<p>Recommended Printing Substrates:</p> <p># :</p> <p>Indicates the substrate may require pretreatment.</p> <p>Ø :</p> <p>Indicates substrate may require flame curing.</p>	<p>COATINGS & PAINTS</p> <p>PowderCoat</p> <p>Surlyn</p> <p>Urethane Paint / Coating</p> <p>Miscellaneous Coatings & Paints</p>	<p>MISCELLANEOUS SUBSTRATES</p> <p>Ceramic</p> <p>Glass</p> <p>Wood</p>	<p>THERMOPLASTICS</p> <p>Acrylonitrile-Butadiene-Styrene</p> <p>Polyphenylene Ether</p> <p>Polyoxymethylene -1 Ø</p> <p>Polybutylene Terephthalate</p> <p>Polymethyl Methacrylate</p> <p>Cellulose Acetate</p> <p>Cellulose Acetate Butyrate</p> <p>Polyphenylene Oxide #</p> <p>Polyamides</p> <p>Polycarbonate</p> <p>Polyester</p> <p>Polyetherimide</p> <p>Polyethylene #</p> <p>Polyethylene Terephthalate</p> <p>Polyimide</p> <p>Polyimide Filaments</p> <p>Polyphenylene Sulfide</p> <p>Polyphenylsulfone</p> <p>Polypropylene #</p> <p>Polysulfone</p> <p>Polyvinyl Chloride Rigid</p>
	<p>METALS</p> <p>Aluminum</p> <p>Anodized Metal</p> <p>Brass</p> <p>Chrome Plate</p> <p>Copper</p> <p>Bronze</p> <p>Iron</p> <p>Steel</p> <p>Tin</p> <p>Titanium</p> <p>Miscellaneous Metals</p>	<p>OTHERS</p> <p>Acrylic Sheets & Molding Powders</p> <p>C-Resin #</p> <p>Formica</p> <p>Hostra</p> <p>Polycarbonate / ABS</p> <p>Thermoplastic Polyester Resin</p> <p>Viton</p>	<p>THERMOSET</p> <p>Epoxy Resin</p> <p>Phenol Formaldehyde Resin</p> <p>Polyester Epoxy Resin</p> <p>Polyurethane, Rigid #</p> <p>Urea Formaldehyde Resin</p>
		<p>FLEXIBLE PLASTICS</p> <p>Urethane, Flexible #</p>	



Trusted Partner for Your Product Decorating Needs

Trans Tech 475 North Gary Avenue, Carol Stream, IL 60188
 Tel +1 (630) 752 4000 Fax +1 (630) 752 4467
 Email sales@itwtranstech.com

www.itwtranstech.com www.itwid.com

A MEMBER OF

