



Trade name: Tampa® Star 1 L TPR 130

Version: 12 /

Date revised: 21.08.2019

Substance number: 38030057130

Replaces Version: 11 /

Print date: 31.03.20

## **SECTION 1: Identification of the substance/mixture and of the company/undertaking**

### **1.1. Product identifier**

Tampa® Star 1 L TPR 130

### **1.2. Relevant identified uses of the substance or mixture and uses advised against**

#### **Use of the substance/preparation**

Pad printing ink

### **1.3. Details of the supplier of the safety data sheet**

#### **Address/Manufacturer**

Marabu GmbH & Co. KG  
Asperger Strasse 4  
71732 Tamm  
Germany

Telephone no. +49-7141/691-0  
Fax no. +49-7141/691-147  
Information provided by / telephone Department product safety  
E-mail address of person responsible PRSI@marabu.com  
for this SDS

### **1.4. Emergency telephone number**

(+49) (0)621-60-43333

## **SECTION 2: Hazards identification**

### **2.1. Classification of the substance or mixture**

#### **Classification (Regulation (EC) No. 1272/2008)**

Classification (Regulation (EC) No. 1272/2008)

Flam. Liq. 3	H226
Eye Dam. 1	H318
STOT SE 3	H335
Aquatic Chronic 3	H412

### **2.2. Label elements**

#### **Labelling according to regulation (EC) No 1272/2008**

##### **Hazard pictograms**



##### **Signal word**

Danger

##### **Hazard statements**

H226	Flammable liquid and vapour.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H412	Harmful to aquatic life with long lasting effects.



Trade name: Tampa® Star 1 L TPR 130

Version: 12 /

Date revised: 21.08.2019

Substance number: 38030057130

Replaces Version: 11 /

Print date: 31.03.20

**Precautionary statements**

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing dust / fume / gas / mist / vapours / spray.
P280	Wear protective gloves / protective clothing / eye protection / face protection.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER or doctor.

**Hazardous component(s) to be indicated on label (Regulation (EC) No. 1272/2008)**

contains	Butyl glycolate; Cyclohexanone; Solvent naphtha (petroleum), light arom. 4-Hydroxy-4-methylpentan-2-one
----------	--

**2.3. Other hazards**

No special hazards have to be mentioned.

**SECTION 3: Composition/information on ingredients****3.2. Mixtures****Chemical characterization**

Pad printing ink based on acrylic resins and on solvents

**Hazardous ingredients****4-Hydroxy-4-methylpentan-2-one**

CAS No.	123-42-2
EINECS no.	204-626-7
Registration no.	01-2119473975-21
Concentration	>= 25 < 50 %

Classification (Regulation (EC) No. 1272/2008)

Flam. Liq. 3	H226
Eye Irrit. 2	H319
STOT SE 3	H335

Concentration limits (Regulation (EC) No. 1272/2008)

Eye Irrit. 2	H319	>= 10
--------------	------	-------

**2-Butoxyethyl acetate**

CAS No.	112-07-2
EINECS no.	203-933-3
Registration no.	01-2119475112-47
Concentration	>= 1 < 10 %

Classification (Regulation (EC) No. 1272/2008)

Acute Tox. 4	H332
Acute Tox. 4	H312
Acute Tox. 4	H302

**Cyclohexanone**

CAS No.	108-94-1
EINECS no.	203-631-1
Registration no.	01-2119453616-35
Concentration	>= 3 < 9 %

Classification (Regulation (EC) No. 1272/2008)

Acute Tox. 4	H332
Flam. Liq. 3	H226



Trade name: Tampa® Star 1 L TPR 130

Version: 12 /

Date revised: 21.08.2019

Substance number: 38030057130

Replaces Version: 11 /

Print date: 31.03.20

Acute Tox. 4	H302
Acute Tox. 4	H312
Eye Dam. 1	H318
Skin Irrit. 2	H315

**Solvent naphtha (petroleum), light arom.**

CAS No.	64742-95-6
EINECS no.	265-199-0
Registration no.	01-2119455851-35 (LIST NUMBER 918-668-5)
Concentration	>= 2,5 < 10 %

Classification (Regulation (EC) No. 1272/2008)

Flam. Liq. 3	H226
STOT SE 3	H336
STOT SE 3	H335
Asp. Tox. 1	H304
Aquatic Chronic 2	H411

**2-Methoxy-1-methylethyl acetate**

CAS No.	108-65-6
EINECS no.	203-603-9
Registration no.	01-2119475791-29
Concentration	>= 1 < 10 %

Classification (Regulation (EC) No. 1272/2008)

Flam. Liq. 3	H226
STOT SE 3	H336

**Butyl glycolate**

CAS No.	7397-62-8
EINECS no.	230-991-7
Registration no.	01-2119514685-36
Concentration	>= 1 < 3 %

Classification (Regulation (EC) No. 1272/2008)

Eye Dam. 1	H318
Repr. 2	H361d

**Polyester of phosphoric acid (72243-070628, Germany)**

Concentration	>= 1 < 10 %
---------------	-------------

Classification (Regulation (EC) No. 1272/2008)

Eye Irrit. 2	H319
--------------	------

**SECTION 4: First aid measures****4.1. Description of first aid measures****General information**

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice.

**After inhalation**

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

**After skin contact**



Trade name: Tampa® Star 1 L TPR 130

Version: 12 /

Date revised: 21.08.2019

Substance number: 38030057130

Replaces Version: 11 /

Print date: 31.03.20

Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

#### **After eye contact**

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

#### **After ingestion**

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

### **4.2. Most important symptoms and effects, both acute and delayed**

Until now no symptoms known so far.

### **4.3. Indication of any immediate medical attention and special treatment needed**

#### **Hints for the physician / treatment**

Treat symptomatically

## **SECTION 5: Firefighting measures**

### **5.1. Extinguishing media**

#### **Suitable extinguishing media**

Recommended: alcohol resistant foam, CO<sub>2</sub>, powders, water spray/mist, Not be used for safety reasons: water jet

### **5.2. Special hazards arising from the substance or mixture**

In the event of fire the following can be released: Carbon monoxide (CO); Carbon dioxide (CO<sub>2</sub>); dense black smoke; Hydrogen chloride (HCl); Nitrogen oxides (NO<sub>x</sub>)

### **5.3. Advice for firefighters**

#### **Special protective equipment for fire-fighting**

Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses.

## **SECTION 6: Accidental release measures**

### **6.1. Personal precautions, protective equipment and emergency procedures**

Exclude sources of ignition and ventilate the area. Avoid breathing vapours. Refer to protective measures listed in Sections 7 and 8.

### **6.2. Environmental precautions**

Do not allow to enter drains or waterways. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

### **6.3. Methods and material for containment and cleaning up**

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent - avoid use of solvents.

### **6.4. Reference to other sections**

Information regarding Safe handling, see Section 7. Information regarding personal protective measures, see Section 8. Information regarding waste disposal, see Section 13.

## **SECTION 7: Handling and storage**

### **7.1. Precautions for safe handling**

#### **Advice on safe handling**

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour



Trade name: Tampa® Star 1 L TPR 130

Version: 12 /

Date revised: 21.08.2019

Substance number: 38030057130

Replaces Version: 11 /

Print date: 31.03.20

concentration higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Isolate from sources of heat, sparks and open flame. No sparking tools should be used. Avoid skin and eye contact. Avoid the inhalation of particulates and spray mist arising from the application of this mixture. Smoking, eating and drinking shall be prohibited in application area. For personal protection see Section 8. Never use pressure to empty: container is not a pressure vessel. Always keep in containers of same material as the original one. Comply with the health and safety at work laws. Do not allow to enter drains or water courses.

**Advice on protection against fire and explosion**

Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

**Classification of fires / temperature class / Ignition group / Dust explosion class**

Classification of fires B (Combustible liquid substances)  
 Temperature class T3

**7.2. Conditions for safe storage, including any incompatibilities**

**Requirements for storage rooms and vessels**

Electrical installations/working materials must comply with the local applied technological safety standards. Storage rooms in which filling operations take place must have a conducting floor. Store in accordance with national regulation

**Hints on storage assembly**

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

**Further information on storage conditions**

Observe label precautions. Store between 15 and 30 °C in a dry, well ventilated place away from sources of heat and direct sunlight. Keep container tightly closed. Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

**7.3. Specific end use(s)**

Pad printing ink

**SECTION 8: Exposure controls/personal protection \*\*\***

**8.1. Control parameters**

**Derived No/Minimal Effect Levels (DNEL/DMEL)**

**4-Hydroxy-4-methylpentan-2-one**

Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Short term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	240	mg/m <sup>3</sup>

Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	32,6	mg/m <sup>3</sup>

Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	

Safety data sheet in accordance with regulation (EC) No 1907/2006



Trade name: Tampa® Star 1 L TPR 130

Version: 12 /

Date revised: 21.08.2019

Substance number: 38030057130

Replaces Version: 11 /

Print date: 31.03.20

Route of exposure dermal  
 Mode of action Systemic effects  
 Concentration 240 mg/kg/d

Type of value Derived No Effect Level (DNEL)  
 Reference group Consumer  
 Duration of exposure Long term  
 Route of exposure inhalative  
 Mode of action Systemic effects  
 Concentration 5,8 mg/m<sup>3</sup>

Type of value Derived No Effect Level (DNEL)  
 Reference group Consumer  
 Duration of exposure Long term  
 Route of exposure oral  
 Mode of action Systemic effects  
 Concentration 1,67 mg/kg/d

Type of value Derived No Effect Level (DNEL)  
 Reference group Consumer  
 Duration of exposure Long term  
 Route of exposure dermal  
 Mode of action Systemic effects  
 Concentration 167 mg/kg/d

**2-Methoxy-1-methylethyl acetate**

Type of value Derived No Effect Level (DNEL)  
 Reference group Worker  
 Duration of exposure Long term  
 Route of exposure dermal  
 Mode of action Systemic effects  
 Concentration 796 mg/kg/d

Type of value Derived No Effect Level (DNEL)  
 Reference group Worker  
 Duration of exposure Long term  
 Route of exposure inhalative  
 Mode of action Systemic effects  
 Concentration 275 mg/m<sup>3</sup>

Type of value Derived No Effect Level (DNEL)  
 Reference group Consumer  
 Duration of exposure Long term  
 Route of exposure dermal  
 Mode of action Systemic effects  
 Concentration 320 mg/kg/d

Type of value Derived No Effect Level (DNEL)  
 Reference group Consumer  
 Duration of exposure Long term  
 Route of exposure inhalative  
 Mode of action Systemic effects  
 Concentration 33 mg/m<sup>3</sup>

Type of value Derived No Effect Level (DNEL)  
 Reference group Consumer  
 Duration of exposure Long term

Safety data sheet in accordance with regulation (EC) No 1907/2006



Trade name: Tampa® Star 1 L TPR 130

Version: 12 /

Date revised: 21.08.2019

Substance number: 38030057130

Replaces Version: 11 /

Print date: 31.03.20

Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	33	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	oral	
Mode of action	Systemic effects	
Concentration	36	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Lifetime	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	550	mg/m <sup>3</sup>
<b>Solvent naphtha (petroleum), light arom.</b>		
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	oral	
Mode of action	Systemic effects	
Concentration	11	mg/kg
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	11	mg/kg
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	32	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	150	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	
Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	25	mg/kg/d

**Butyl glycolate**

Type of value	Derived No Effect Level (DNEL)
Reference group	Worker

Safety data sheet in accordance with regulation (EC) No 1907/2006



Trade name: Tampa® Star 1 L TPR 130

Version: 12 /

Date revised: 21.08.2019

Substance number: 38030057130

Replaces Version: 11 /

Print date: 31.03.20

Duration of exposure Long term  
 Route of exposure dermal  
 Mode of action Systemic effects  
 Concentration 10 mg/kg/d

Type of value Derived No Effect Level (DNEL)  
 Reference group Worker  
 Duration of exposure Long term  
 Route of exposure inhalative  
 Mode of action Systemic effects  
 Concentration 7,05 mg/m³

Type of value Derived No Effect Level (DNEL)  
 Reference group Consumer  
 Duration of exposure Long term  
 Route of exposure dermal  
 Mode of action Systemic effects  
 Concentration 25 mg/kg/d

Type of value Derived No Effect Level (DNEL)  
 Reference group Consumer  
 Duration of exposure Long term  
 Route of exposure inhalative  
 Mode of action Systemic effects  
 Concentration 1,74 mg/m³

**2-Butoxyethyl acetate**

Reference substance 2-Butoxyethyl acetate  
 Type of value Derived No Effect Level (DNEL)  
 Reference group Worker  
 Duration of exposure Long term  
 Route of exposure inhalative  
 Mode of action Systemic effects  
 Concentration 133 mg/m³

Type of value 2-Butoxyethyl acetate  
 Reference group Derived No Effect Level (DNEL)  
 Worker  
 Duration of exposure Short term  
 Route of exposure inhalative  
 Mode of action Local effects  
 Concentration 333 mg/m³

Type of value 2-Butoxyethyl acetate  
 Reference group Derived No Effect Level (DNEL)  
 Worker  
 Duration of exposure Long term  
 Route of exposure dermal  
 Mode of action Systemic effects  
 Concentration 169 mg/kg/d

Type of value 2-Butoxyethyl acetate  
 Reference group Derived No Effect Level (DNEL)  
 Worker  
 Duration of exposure Short term  
 Route of exposure dermal  
 Mode of action Systemic effects



Safety data sheet in accordance with regulation (EC) No 1907/2006



Trade name: Tampa® Star 1 L TPR 130

Version: 12 /

Date revised: 21.08.2019

Substance number: 38030057130

Replaces Version: 11 /

Print date: 31.03.20

Concentration	120	mg/kg/d
Type of value	2-Butoxyethyl acetate	
Reference group	Derived No Effect Level (DNEL)	
Duration of exposure	General Population	
Route of exposure	Long term	
Mode of action	inhalative	
Concentration	Systemic effects	
	80	mg/m <sup>3</sup>
Type of value	2-Butoxyethyl acetate	
Reference group	Derived No Effect Level (DNEL)	
Duration of exposure	General Population	
Route of exposure	Short term	
Mode of action	inhalative	
Concentration	Local effects	
	200	mg/m <sup>3</sup>
Type of value	2-Butoxyethyl acetate	
Reference group	Derived No Effect Level (DNEL)	
Duration of exposure	General Population	
Route of exposure	Long term	
Mode of action	dermal	
Concentration	Systemic effects	
	102	mg/kg/d
Type of value	2-Butoxyethyl acetate	
Reference group	Derived No Effect Level (DNEL)	
Duration of exposure	General Population	
Route of exposure	Short term	
Mode of action	dermal	
Concentration	Systemic effects	
	72	mg/kg/d
Type of value	2-Butoxyethyl acetate	
Reference group	Derived No Effect Level (DNEL)	
Duration of exposure	General Population	
Route of exposure	Long term	
Mode of action	oral	
Concentration	Systemic effects	
	8,6	mg/kg/d
Type of value	2-Butoxyethyl acetate	
Reference group	Derived No Effect Level (DNEL)	
Duration of exposure	General Population	
Route of exposure	Short term	
Mode of action	oral	
Concentration	Systemic effects	
	36	mg/kg/d
<b>Cyclohexanone</b>		
Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	100	mg/m <sup>3</sup>

Safety data sheet in accordance with regulation (EC) No 1907/2006



Trade name: Tampa® Star 1 L TPR 130

Version: 12 /

Date revised: 21.08.2019

Substance number: 38030057130

Replaces Version: 11 /

Print date: 31.03.20

Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Short term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	100	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	
Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	10	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Short term	
Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	100	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Short term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	50	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Short term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	50	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Short term	
Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	30	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Short term	
Route of exposure	oral	
Mode of action	Systemic effects	
Concentration	10	mg/kg/d

**Predicted No Effect Concentration (PNEC)**

**4-Hydroxy-4-methylpentan-2-one**

Type of value	PNEC	
Type	Freshwater	
Concentration	2	mg/kg
Type of value	PNEC	



Trade name: Tampa® Star 1 L TPR 130

Version: 12 /

Date revised: 21.08.2019

Substance number: 38030057130

Replaces Version: 11 /

Print date: 31.03.20

Type	Saltwater	
Concentration	0,2	mg/kg
Type of value	PNEC	
Type	Sewage treatment plant (STP)	
Concentration	82	mg/kg
Type of value	PNEC	
Type	Freshwater sediment	
Concentration	9,06	mg/kg/d
Type of value	PNEC	
Type	Marine sediment	
Concentration	0,91	mg/kg/d
Type of value	PNEC	
Type	Soil	
Concentration	0,63	mg/kg/d

**2-Methoxy-1-methylethyl acetate**

Reference substance	2-Methoxy-1-methylethyl acetate	
Type of value	PNEC	
Type	Freshwater	
Concentration	0,635	mg/l
Type of value	PNEC	
Type	Freshwater sediment	
Concentration	3,29	mg/kg
Type of value	PNEC	
Type	Soil	
Concentration	0,29	mg/kg
Source	Literature value	
Type of value	PNEC	
Type	Sewage treatment plant (STP)	
Concentration	100	mg/l
Source	Literature value	
Type of value	PNEC	
Type	Marine sediment	
Concentration	0,329	mg/kg
Source	Literature value	
Type of value	PNEC	
Type	Saltwater	
Concentration	0,0635	mg/l

**Butyl glycolate**

Type of value	PNEC	
Type	Freshwater	
Concentration	0,05	mg/l
Type of value	PNEC	
Type	Soil	
Concentration	0,011	mg/kg

Safety data sheet in accordance with regulation (EC) No 1907/2006



Trade name: Tampa® Star 1 L TPR 130

Version: 12 /

Date revised: 21.08.2019

Substance number: 38030057130

Replaces Version: 11 /

Print date: 31.03.20

Type of value PNEC  
 Type Freshwater sediment  
 Concentration 0,203 mg/kg

Type of value PNEC  
 Type Sewage treatment plant (STP)  
 Concentration 232 mg/l

Type of value PNEC  
 Type Saltwater  
 Concentration 0,005 mg/l

Type of value PNEC  
 Type Marine sediment  
 Concentration 0,02 mg/kg

**2-Butoxyethyl acetate**

Reference substance 2-Butoxyethyl acetate  
 Type of value PNEC  
 Type Water  
 Concentration 0,304 mg/l  
 Source Literature value

Type of value 2-Butoxyethyl acetate  
 Type PNEC  
 Type Aquatic  
 Concentration 0,0304 g/l  
 Source Literature value

Type of value 2-Butoxyethyl acetate  
 Type PNEC  
 Type Sediment  
 Concentration 2,03 mg/kg  
 Source Literature value

Type of value 2-Butoxyethyl acetate  
 Type PNEC  
 Type Marine sediment  
 Concentration 0,203 mg/kg  
 Source Literature value

Type of value 2-Butoxyethyl acetate  
 Type PNEC  
 Type Soil  
 Concentration 0,68 mg/kg  
 Source Literature value

**Cyclohexanone**

Type of value PNEC  
 Type Freshwater  
 Concentration 0,0329 mg/l

Type of value PNEC  
 Type Saltwater  
 Concentration 0,00329 mg/l

Type of value PNEC



Trade name: Tampa® Star 1 L TPR 130

Version: 12 /

Date revised: 21.08.2019

Substance number: 38030057130

Replaces Version: 11 /

Print date: 31.03.20

Type	Water (intermittent release)	
Concentration	0,329	mg/l
Type of value	PNEC	
Type	Sewage treatment plant (STP)	
Concentration	10	mg/l
Type of value	PNEC	
Type	Freshwater sediment	
Concentration	0,0951	mg/kg
Type of value	PNEC	
Type	Soil	
Concentration	0,0143	mg/kg

## 8.2. Exposure controls

### Exposure controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

### Respiratory protection

If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators. Full mask, filter A

### Hand protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

For prolonged or repeated handling nitrile rubber gloves with textile undergloves are required.

Material thickness > 0,5 mm

Breakthrough time < 30 min

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occurred.

### Eye protection

Use safety eyewear designed to protect against splash of liquids.

### Body protection

Cotton or cotton/synthetic overalls or coveralls are normally suitable.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>Form</b>	Pasty
<b>Colour</b>	coloured
<b>Odour</b>	solvent-like

#### Odour threshold

Remarks No data available

#### pH value

Remarks Not applicable



Trade name: Tampa® Star 1 L TPR 130

Version: 12 /

Date revised: 21.08.2019

Substance number: 38030057130

Replaces Version: 11 /

Print date: 31.03.20

**Melting point**

Remarks not determined

**Freezing point**

Remarks not determined

**Initial boiling point and boiling range**

Value	appr. 153		°C
Pressure	1.013	hPa	
Source	Literature value		

**Flash point**

Value	57		°C
Method	ASTM D 6450 (CCCFP)		

**Evaporation rate (ether = 1) :**

Remarks not determined

**Flammability (solid, gas)**

Not applicable

**Upper/lower flammability or explosive limits**

Lower explosion limit	appr. 0,7	%(V)
Upper explosion limit	appr. 9,4	%(V)
Source	Literature value	

**Vapour pressure**

Value	appr. 3		hPa
Temperature	20	°C	
Method	calculated		

**Vapour density**

Remarks not determined

**Density**

Value	1,12		g/cm <sup>3</sup>
Temperature	20	°C	

**Solubility in water**

Remarks partially miscible

**Partition coefficient: n-octanol/water**

Remarks Not applicable

**Ignition temperature**

Value	appr. 280	°C
Source	Literature value	

**Efflux time**

Value	> 150	s
Method	DIN 53211 4 mm	

**Explosive properties**

evaluation no

**Oxidising properties**

evaluation None known

**9.2. Other information****Other information**

The physical specifications are approximate values and refer to the used safety relevant component(s).

**SECTION 10: Stability and reactivity**



Trade name: Tampa® Star 1 L TPR 130

Version: 12 /

Date revised: 21.08.2019

Substance number: 38030057130

Replaces Version: 11 /

Print date: 31.03.20

**10.1. Reactivity**

No hazardous reactions when stored and handled according to prescribed instructions.

**10.2. Chemical stability**

Stable under recommended storage and handling conditions (see section 7).

**10.3. Possibility of hazardous reactions**

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

**10.4. Conditions to avoid**

When exposed to high temperatures may produce hazardous decomposition products.

**10.5. Incompatible materials**

No hazardous reactions when stored and handled according to prescribed instructions.

**10.6. Hazardous decomposition products**

See chapter 5.2 (Firefighting measures - Special hazards arising from the substance or mixture).

**SECTION 11: Toxicological information****11.1. Information on toxicological effects****Acute oral toxicity**

ATE	>	2.000	mg/kg
Method	calculated value (Regulation (EC) No. 1272/2008)		

**Acute oral toxicity (Components)****4-Hydroxy-4-methylpentan-2-one**

Species	rat		
LD50		3002	mg/kg
Method	OECD 401		

**Butyl glycolate**

Species	rat		
LD50		4595	mg/kg

**2-Butoxyethyl acetate**

Species	rat		
LD50		1880	mg/kg
Method	OECD 401		

**Cyclohexanone**

Species	rat		
LD50		1620	mg/kg

**Acute dermal toxicity**

ATE	>	2.000	mg/kg
Method	calculated value (Regulation (EC) No. 1272/2008)		

**Acute dermal toxicity (Components)****4-Hydroxy-4-methylpentan-2-one**

Species	rabbit		
LD50		13500	mg/kg

**2-Butoxyethyl acetate**

Species	rabbit		
LD50		1480	mg/kg

**Acute inhalational toxicity**

ATE	>	20	mg/l
Administration/Form	Vapors		
Method	calculated value (Regulation (EC) No. 1272/2008)		



Trade name: Tampa® Star 1 L TPR 130

Version: 12 /

Date revised: 21.08.2019

Substance number: 38030057130

Replaces Version: 11 /

Print date: 31.03.20

ATE > 5 mg/l  
 Administration/Form Dust/Mist  
 Method calculated value (Regulation (EC) No. 1272/2008)  
 Remarks Based on available data, the classification criteria are not met.

**Acute inhalative toxicity (Components)**

**4-Hydroxy-4-methylpentan-2-one**

Species rat  
 LD0 7,6 mg/l  
 Duration of exposure 4 h  
 Administration/Form Vapors  
 Method OECD 403

**2-Butoxyethyl acetate**

Species rat  
 LD0 2,66 mg/l  
 Duration of exposure 4 h  
 Administration/Form Vapors  
 Method OECD 403

**Cyclohexanone**

Species rat  
 LC50 > 6,2 mg/l  
 Duration of exposure 4 h  
 Administration/Form Vapors

**Skin corrosion/irritation**

Remarks Based on available data, the classification criteria are not met.

**Skin corrosion/irritation (Components)**

**4-Hydroxy-4-methylpentan-2-one**

Species rabbit  
 evaluation slight irritant effect - does not require labelling

**2-Methoxy-1-methylethyl acetate**

Species rabbit  
 evaluation non-irritant

**Serious eye damage/irritation**

evaluation corrosive  
 Remarks The classification criteria are met.

**Serious eye damage/irritation (Components)**

**4-Hydroxy-4-methylpentan-2-one**

Species rabbit  
 evaluation irritant  
 Method EEC 84/449, B.5

**Sensitization**

Remarks Based on available data, the classification criteria are not met.

**Sensitization (Components)**

**4-Hydroxy-4-methylpentan-2-one**

Species guinea pig  
 evaluation non-sensitizing  
 Method OECD 406

**Mutagenicity**

Remarks Based on available data, the classification criteria are not met.

**Reproductive toxicity**

Remarks Based on available data, the classification criteria are not met.

**Carcinogenicity**





Trade name: Tampa® Star 1 L TPR 130

Version: 12 /

Date revised: 21.08.2019

Substance number: 38030057130

Replaces Version: 11 /

Print date: 31.03.20

Remarks Based on available data, the classification criteria are not met.

**Specific Target Organ Toxicity (STOT)****Single exposure**Remarks The classification criteria are met.  
evaluation May cause respiratory irritation.**Repeated exposure**

Remarks Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Experience in practice**

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation. Causes serious eye damage. Ingestion may cause nausea, diarrhoea and vomiting. Ingredient butyl glycolate may possibly cause harm to the unborn child if ingested. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

**Other information**

There are no data available on the mixture itself.

The mixture has been assessed following the additivity method of the CLP Regulation (EC) No 1272/2008 and classified for toxicological hazards accordingly.

**SECTION 12: Ecological information****12.1. Toxicity****General information**

There are no data available on the mixture itself. Do not allow to enter drains or water courses. The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is classified for eco-toxicological properties accordingly. See Sections 2 and 3 for details.

**Fish toxicity (Components)****4-Hydroxy-4-methylpentan-2-one**

Species	red killifish		
LC50	> 100		mg/l
Duration of exposure	96	h	

**4-Hydroxy-4-methylpentan-2-one**

Species	Menicia beryllina		
LC50	420000		µg/l

**Solvent naphtha (petroleum), light arom.**

Species	rainbow trout (Oncorhynchus mykiss)		
LL50	9,2		mg/l
Duration of exposure	96	h	

**2-Butoxyethyl acetate**

Species	golden orfe (Leuciscus idus)		
LC50	80		mg/l
Duration of exposure	48	h	

**Cyclohexanone**

Species	Fathead minnow (Pimephales promelas)		
LC50	630000		µg/l



Trade name: Tampa® Star 1 L TPR 130

Version: 12 /

Date revised: 21.08.2019

Substance number: 38030057130

Replaces Version: 11 /

Print date: 31.03.20

**Daphnia toxicity (Components)****4-Hydroxy-4-methylpentan-2-one**

Species	Daphnia magna		
EC50	> 1000		mg/l
Duration of exposure	48	h	

**Solvent naphtha (petroleum), light arom.**

EL50	3,2		mg/l
Duration of exposure	48	h	

**2-Butoxyethyl acetate**

Species	Daphnia magna		
EC50	37		mg/l
Duration of exposure	48	h	

**Algae toxicity (Components)****4-Hydroxy-4-methylpentan-2-one**

Species	Desmodesmus		
ErC50	> 1000		mg/l
Duration of exposure	72	h	

**4-Hydroxy-4-methylpentan-2-one**

Species	Desmodesmus		
NOEC	1000		mg/l
Duration of exposure	72	h	

**Solvent naphtha (petroleum), light arom.**

Species	Desmodesmus		
ErC50	0,42		mg/l
Duration of exposure	72	h	

**Solvent naphtha (petroleum), light arom.**

Species	Pseudokirchneriella subcapitata		
EC50	0,29		mg/l
Duration of exposure	72	h	
Source	REACH registration dossier		

**2-Butoxyethyl acetate**

EC50	> 500		mg/l
Duration of exposure	72	h	

**Bacteria toxicity (Components)****2-Butoxyethyl acetate**

Species	Pseudomonas putida		
EC10	720		mg/l
Duration of exposure	17	h	
Method	OECD 209		

**12.2. Persistence and degradability****General information**

No data available

**Biodegradability (Components)****4-Hydroxy-4-methylpentan-2-one**

Value	98,51		%
Duration of test evaluation	28	d	
	Readily biodegradable (according to OECD criteria)		

**2-Butoxyethyl acetate**

Value	88		%
Duration of test evaluation	28	d	
	Readily biodegradable (according to OECD criteria)		



Trade name: Tampa® Star 1 L TPR 130

Version: 12 /

Date revised: 21.08.2019

Substance number: 38030057130

Replaces Version: 11 /

Print date: 31.03.20

Method OECD 301 C

### 12.3. Bioaccumulative potential

#### General information

There are no data available on the mixture itself.

#### Partition coefficient: n-octanol/water

Remarks Not applicable

### 12.4. Mobility in soil

#### General information

There are no data available on the mixture itself.

### 12.5. Results of PBT and vPvB assessment

#### General information

There are no data available on the mixture itself.

### 12.6. Other adverse effects

#### General information

There are no data available on the mixture itself.

## **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

#### Disposal recommendations for the product

Do not allow to enter drains or water courses.

Wastes and emptied containers should be classified in accordance with relevant national regulation.

The European Waste Catalogue classification of this product, when disposed of as waste is

EWC waste code 08 03 12\* waste ink containing dangerous substances

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

For further information contact your local waste authority.

#### Disposal recommendations for packaging

Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers.

Empty containers must be scrapped or reconditioned.

Not emptied containers are hazardous waste (waste code number 150110).

## **SECTION 14: Transport information**

Safety data sheet in accordance with regulation (EC) No 1907/2006



Trade name: Tampa® Star 1 L TPR 130




Version: 12 /

Date revised: 21.08.2019

Substance number: 38030057130

Replaces Version: 11 /

Print date: 31.03.20

	Land transport ADR/RID	Marine transport IMDG/GGVSee	Air transport ICAO/IATA
Tunnel restriction code	D/E		
14.1. UN number	1263	1263	1263
14.2. UN proper shipping name	PAINT	PAINT	PAINT
14.3. Transport hazard class(es)	3	3	3
Label			
14.4. Packing group	III	III	III
Special provision	640E		
Remarks	The product is viscous; non-dangerous good in Containers with not more than 450 ltrs.	Transport according to 2.3.2.5 of the IMDG Code	
Limited Quantity	5 l		
Transport category	3		
14.5. Environmental hazards	-	no	-

**Information for all modes of transport**

**14.6. Special precautions for user**

Transport within the user's premises:  
Always transport in closed containers that are upright and secure.  
Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**Other information**

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

no

**SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**Other information**

All components are contained in the PICCS inventory.  
All components are contained in the DSL inventory.  
All components are contained in the ECL inventory.

**15.2. Chemical safety assessment**

For this preparation a chemical safety assessment has not been carried out.



Trade name: Tampa® Star 1 L TPR 130

Version: 12 /

Date revised: 21.08.2019

Substance number: 38030057130

Replaces Version: 11 /

Print date: 31.03.20

## **SECTION 16: Other information**

### **Hazard statements listed in Chapter 3**

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H411	Toxic to aquatic life with long lasting effects.

### **CLP categories listed in Chapter 3**

Acute Tox. 4	Acute toxicity, Category 4
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Dam. 1	Serious eye damage, Category 1
Eye Irrit. 2	Eye irritation, Category 2
Flam. Liq. 3	Flammable liquid, Category 3
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin irritation, Category 2
STOT SE 3	Specific target organ toxicity - single exposure, Category 3

### **Supplemental information**

Relevant changes compared with the previous version of the safety data sheet are marked with: \*\*\*  
 This information is based on our present state of knowledge. However, it should not constitute a guarantee for any specific product properties and shall not establish a legally valid relationship.  
 The information in this Safety Data Sheet is based on the present state of knowledge and current legislation.

It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.  
 The product should not be used for purposes other than those shown in Section 1 without first referring to the supplier and obtaining written handling instructions.

As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with.

The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation.