



Trade name: Tampa® Pur 1 KG TPU 930

Version: 11 /

Date revised: 23.08.2019

Substance number: 38050057930

Replaces Version: 10 /

Print date: 31.03.20

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Tampa® Pur 1 KG TPU 930

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/preparation

Pad printing ink

1.3. Details of the supplier of the safety data sheet

Address/Manufacturer

Marabu GmbH & Co. KG
Asperger Strasse 4
71732 Tamm
Germany
Telephone no. +49-7141/691-0
Fax no. +49-7141/691-147
Information provided by / telephone Department product safety
E-mail address of person responsible PRSI@marabu.com
for this SDS

1.4. Emergency telephone number

(+49) (0)621-60-43333

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (Regulation (EC) No. 1272/2008)

Classification (Regulation (EC) No. 1272/2008)

Flam. Liq. 3	H226
Eye Dam. 1	H318
Repr. 2	H361d
Aquatic Chronic 3	H412
STOT SE 3	H336

2.2. Label elements

Labelling according to regulation (EC) No 1272/2008

Hazard pictograms



Signal word

Danger

Hazard statements

H226	Flammable liquid and vapour.
H318	Causes serious eye damage.
H361d	Suspected of damaging the unborn child.
H412	Harmful to aquatic life with long lasting effects.



Trade name: Tampa® Pur 1 KG TPU 930

Version: 11 /

Date revised: 23.08.2019

Substance number: 38050057930

Replaces Version: 10 /

Print date: 31.03.20

H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 Avoid breathing dust / fume / gas / mist / vapours / spray.

P280 Wear protective gloves / protective clothing / eye protection / face protection.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER or doctor.

Hazardous component(s) to be indicated on label (Regulation (EC) No. 1272/2008)

contains Butyl glycolate; Solvent naphtha (petroleum), light arom. 2-Methoxy-1-methylethyl acetate; n-Butyl acetate

2.3. Other hazards

No special hazards have to be mentioned.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Chemical characterization**

Pad printing ink based on acrylic resins and on solvents

Hazardous ingredients**Solvent naphtha (petroleum), light arom.**

CAS No. 64742-95-6

EINECS no. 265-199-0

Registration no. 01-2119455851-35 (LIST NUMBER 918-668-5)

Concentration >= 2,5 < 10 %

Classification (Regulation (EC) No. 1272/2008)

Flam. Liq. 3	H226
STOT SE 3	H336
STOT SE 3	H335
Asp. Tox. 1	H304
Aquatic Chronic 2	H411

n-Butyl acetate

CAS No. 123-86-4

EINECS no. 204-658-1

Registration no. 01-2119485493-29

Concentration >= 1 < 10 %

Classification (Regulation (EC) No. 1272/2008)

Flam. Liq. 3	H226
STOT SE 3	H336

Xylene

CAS No. 1330-20-7

EINECS no. 215-535-7

Registration no. 01-2119488216-32/01-2119486136-34

Concentration >= 1 < 10 %

Classification (Regulation (EC) No. 1272/2008)

Skin Irrit. 2	H315
Flam. Liq. 3	H226



Trade name: Tampa® Pur 1 KG TPU 930

Version: 11 /

Date revised: 23.08.2019

Substance number: 38050057930

Replaces Version: 10 /

Print date: 31.03.20

Acute Tox. 4	H332
Acute Tox. 4	H312
Eye Irrit. 2	H319
STOT SE 3	H335
STOT RE 2	H373
Asp. Tox. 1	H304
Aquatic Chronic 3	H412

2-Methoxy-1-methylethyl acetate

CAS No.	108-65-6
EINECS no.	203-603-9
Registration no.	01-2119475791-29
Concentration	>= 1 < 10 %

Classification (Regulation (EC) No. 1272/2008)

Flam. Liq. 3	H226
STOT SE 3	H336

Butyl glycolate

CAS No.	7397-62-8
EINECS no.	230-991-7
Registration no.	01-2119514685-36
Concentration	>= 3 < 10 %

Classification (Regulation (EC) No. 1272/2008)

Eye Dam. 1	H318
Repr. 2	H361d

Ethyl benzene

CAS No.	100-41-4
EINECS no.	202-849-4
Registration no.	01-2119489370-35
Concentration	>= 1 < 5,3 %

Classification (Regulation (EC) No. 1272/2008)

Flam. Liq. 2	H225
Acute Tox. 4	H332
STOT RE 2	H373
Asp. Tox. 1	H304
Aquatic Chronic 3	H412
	Ear

Alcohols, C16-18, ethoxylated > 20 EO

CAS No.	68439-49-6
Concentration	>= 1 < 10 %

Classification (Regulation (EC) No. 1272/2008)

Eye Irrit. 2	H319
--------------	------

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice.



Trade name: Tampa® Pur 1 KG TPU 930

Version: 11 /

Date revised: 23.08.2019

Substance number: 38050057930

Replaces Version: 10 /

Print date: 31.03.20

After inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

After skin contact

Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

After eye contact

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Until now no symptoms known so far.

4.3. Indication of any immediate medical attention and special treatment needed

Hints for the physician / treatment

Treat symptomatically

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Recommended: alcohol resistant foam, CO₂, powders, water spray/mist, Not be used for safety reasons: water jet

5.2. Special hazards arising from the substance or mixture

In the event of fire the following can be released: Carbon dioxide (CO₂); Carbon monoxide (CO); dense black smoke; Metal oxides; Silicon dioxide; Nitrogen oxides (NO_x); Hydrogen chloride (HCl)

5.3. Advice for firefighters

Special protective equipment for fire-fighting

Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Exclude sources of ignition and ventilate the area. Avoid breathing vapours. Refer to protective measures listed in Sections 7 and 8.

6.2. Environmental precautions

Do not allow to enter drains or waterways. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent - avoid use of solvents.

6.4. Reference to other sections

Information regarding Safe handling, see Section 7. Information regarding personal protective measures, see Section 8. Information regarding waste disposal, see Section 13.



Trade name: Tampa® Pur 1 KG TPU 930

Version: 11 /

Date revised: 23.08.2019

Substance number: 38050057930

Replaces Version: 10 /

Print date: 31.03.20

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Isolate from sources of heat, sparks and open flame. No sparking tools should be used. Avoid skin and eye contact. Avoid the inhalation of particulates and spray mist arising from the application of this mixture. Smoking, eating and drinking shall be prohibited in application area. For personal protection see Section 8. Never use pressure to empty: container is not a pressure vessel. Always keep in containers of same material as the original one. Comply with the health and safety at work laws. Do not allow to enter drains or water courses.

Advice on protection against fire and explosion

Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

Classification of fires / temperature class / Ignition group / Dust explosion class

Classification of fires	B (Combustible liquid substances)
Temperature class	T2

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Electrical installations/working materials must comply with the local applied technological safety standards. Storage rooms in which filling operations take place must have a conducting floor. Store in accordance with national regulation

Hints on storage assembly

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

Further information on storage conditions

Observe label precautions. Store between 15 and 30 °C in a dry, well ventilated place away from sources of heat and direct sunlight. Keep container tightly closed. Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

7.3. Specific end use(s)

Pad printing ink

SECTION 8: Exposure controls/personal protection ***

8.1. Control parameters

Derived No/Minimal Effect Levels (DNEL/DMEL)

2-Methoxy-1-methylethyl acetate

Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	
Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	796	mg/kg/d

Type of value	Derived No Effect Level (DNEL)
Reference group	Worker
Duration of exposure	Long term

Safety data sheet in accordance with regulation (EC) No 1907/2006



Trade name: Tampa® Pur 1 KG TPU 930

Version: 11 /

Date revised: 23.08.2019

Substance number: 38050057930

Replaces Version: 10 /

Print date: 31.03.20

Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	275	mg/m ³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	320	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	33	mg/m ³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	33	mg/m ³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	oral	
Mode of action	Systemic effects	
Concentration	36	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Lifetime	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	550	mg/m ³
Xylene		
Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	221	mg/m ³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Short term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	442	mg/m ³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	

Safety data sheet in accordance with regulation (EC) No 1907/2006



Trade name: Tampa® Pur 1 KG TPU 930

Version: 11 /

Date revised: 23.08.2019

Substance number: 38050057930

Replaces Version: 10 /

Print date: 31.03.20

Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	221	mg/m ³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Short term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	442	mg/m ³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	
Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	212	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	65,3	mg/m ³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Short term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	260	mg/m ³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	65,3	mg/m ³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Short term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	260	mg/m ³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	125	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	oral	
Mode of action	Systemic effects	

Safety data sheet in accordance with regulation (EC) No 1907/2006



Trade name: Tampa® Pur 1 KG TPU 930

Version: 11 /

Date revised: 23.08.2019

Substance number: 38050057930

Replaces Version: 10 /

Print date: 31.03.20

Concentration 12,5 mg/kg/d

n-Butyl acetate

Type of value Derived No Effect Level (DNEL)
 Reference group Worker
 Duration of exposure Short term
 Route of exposure inhalative
 Mode of action Systemic effects
 Concentration 960 mg/m³

Type of value Derived No Effect Level (DNEL)
 Reference group Worker
 Duration of exposure Short term
 Route of exposure inhalative
 Mode of action Local effects
 Concentration 960 mg/m³

Type of value Derived No Effect Level (DNEL)
 Reference group Worker
 Duration of exposure Long term
 Route of exposure inhalative
 Mode of action Systemic effects
 Concentration 300 mg/m³

Type of value Derived No Effect Level (DNEL)
 Reference group Worker
 Duration of exposure Long term
 Route of exposure inhalative
 Mode of action Local effects
 Concentration 480 mg/m³

Type of value Derived No Effect Level (DNEL)
 Reference group General Population
 Duration of exposure Short term
 Route of exposure inhalative
 Mode of action Systemic effects
 Concentration 859,7 mg/m³

Type of value Derived No Effect Level (DNEL)
 Reference group General Population
 Duration of exposure Short term
 Route of exposure inhalative
 Mode of action Local effects
 Concentration 859,7 mg/m³

Type of value Derived No Effect Level (DNEL)
 Reference group General Population
 Duration of exposure Long term
 Route of exposure inhalative
 Mode of action Systemic effects
 Concentration 102,34 mg/m³

Type of value Derived No Effect Level (DNEL)
 Reference group General Population
 Duration of exposure Long term
 Route of exposure inhalative
 Mode of action Local effects

Safety data sheet in accordance with regulation (EC) No 1907/2006



Trade name: Tampa® Pur 1 KG TPU 930

Version: 11 /

Date revised: 23.08.2019

Substance number: 38050057930

Replaces Version: 10 /

Print date: 31.03.20

Concentration	102,34	mg/m ³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	
Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	11	mg/kg/d

Butyl glycolate

Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	
Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	10	mg/kg/d

Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	7,05	mg/m ³

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	25	mg/kg/d

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	1,74	mg/m ³

Solvent naphtha (petroleum), light arom.

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	oral	
Mode of action	Systemic effects	
Concentration	11	mg/kg

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	11	mg/kg

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	inhalative	

Safety data sheet in accordance with regulation (EC) No 1907/2006



Trade name: Tampa® Pur 1 KG TPU 930

Version: 11 /

Date revised: 23.08.2019

Substance number: 38050057930

Replaces Version: 10 /

Print date: 31.03.20

Mode of action Systemic effects
 Concentration 32 mg/m³

Type of value Derived No Effect Level (DNEL)
 Reference group Worker
 Duration of exposure Long term
 Route of exposure inhalative

Mode of action Systemic effects
 Concentration 150 mg/m³

Type of value Derived No Effect Level (DNEL)
 Reference group Worker
 Duration of exposure Long term
 Route of exposure dermal

Mode of action Systemic effects
 Concentration 25 mg/kg/d

Ethyl benzene

Type of value Derived No Effect Level (DNEL)
 Reference group Worker
 Duration of exposure Long term
 Route of exposure inhalative

Mode of action Systemic effects
 Concentration 77 mg/m³

Type of value Derived No Effect Level (DNEL)
 Reference group Worker
 Duration of exposure Long term
 Route of exposure inhalative

Mode of action Local effects
 Concentration 293 mg/m³

Type of value Derived No Effect Level (DNEL)
 Reference group Worker
 Duration of exposure Long term
 Route of exposure dermal

Mode of action Systemic effects
 Concentration 180 mg/kg/d

Type of value Derived No Effect Level (DNEL)
 Reference group Consumer
 Duration of exposure Long term
 Route of exposure inhalative

Mode of action Systemic effects
 Concentration 15 mg/m³

Type of value Derived No Effect Level (DNEL)
 Reference group Consumer
 Duration of exposure Long term
 Route of exposure oral

Mode of action Systemic effects
 Concentration 1,6 mg/kg/d

Predicted No Effect Concentration (PNEC)

2-Methoxy-1-methylethyl acetate

Reference substance 2-Methoxy-1-methylethyl acetate
 Type of value PNEC

Safety data sheet in accordance with regulation (EC) No 1907/2006



Trade name: Tampa® Pur 1 KG TPU 930

Version: 11 /

Date revised: 23.08.2019

Substance number: 38050057930

Replaces Version: 10 /

Print date: 31.03.20

Type	Freshwater	
Concentration	0,635	mg/l
Type of value	PNEC	
Type	Freshwater sediment	
Concentration	3,29	mg/kg
Type of value	PNEC	
Type	Soil	
Concentration	0,29	mg/kg
Source	Literature value	
Type of value	PNEC	
Type	Sewage treatment plant (STP)	
Concentration	100	mg/l
Source	Literature value	
Type of value	PNEC	
Type	Marine sediment	
Concentration	0,329	mg/kg
Source	Literature value	
Type of value	PNEC	
Type	Saltwater	
Concentration	0,0635	mg/l

Xylene

Type of value	PNEC	
Type	Freshwater	
Concentration	0,327	mg/l
Type of value	PNEC	
Type	Saltwater	
Concentration	0,327	mg/l
Type of value	PNEC	
Type	Freshwater sediment	
Concentration	12,46	mg/kg
Type of value	PNEC	
Type	Marine sediment	
Concentration	12,46	mg/kg
Type of value	PNEC	
Type	Soil	
Concentration	2,31	mg/kg
Type of value	PNEC	
Type	Sewage treatment plant (STP)	
Concentration	6,58	mg/l
Type of value	PNEC	
Type	Water (intermittent release)	
Concentration	0,327	mg/l

n-Butyl acetate

Type of value	PNEC	
---------------	------	--

Safety data sheet in accordance with regulation (EC) No 1907/2006



Trade name: Tampa® Pur 1 KG TPU 930

Version: 11 /

Date revised: 23.08.2019

Substance number: 38050057930

Replaces Version: 10 /

Print date: 31.03.20

Type	Freshwater	
Concentration	0,18	mg/l
Type of value	PNEC	
Type	Saltwater	
Concentration	0,018	mg/l
Type of value	PNEC	
Type	Freshwater sediment	
Concentration	0,981	mg/kg
Type of value	PNEC	
Type	Marine sediment	
Concentration	0,0981	mg/kg
Type of value	PNEC	
Type	Soil	
Concentration	0,0903	mg/kg
Type of value	PNEC	
Type	Sewage treatment plant (STP)	
Concentration	35,6	mg/l
Type of value	PNEC	
Type	Water (intermittent release)	
Concentration	0,36	mg/l
Butyl glycolate		
Type of value	PNEC	
Type	Freshwater	
Concentration	0,05	mg/l
Type of value	PNEC	
Type	Soil	
Concentration	0,011	mg/kg
Type of value	PNEC	
Type	Freshwater sediment	
Concentration	0,203	mg/kg
Type of value	PNEC	
Type	Sewage treatment plant (STP)	
Concentration	232	mg/l
Type of value	PNEC	
Type	Saltwater	
Concentration	0,005	mg/l
Type of value	PNEC	
Type	Marine sediment	
Concentration	0,02	mg/kg
Ethyl benzene		
Type of value	PNEC	
Type	Freshwater	
Concentration	0,1	mg/l



Trade name: Tampa® Pur 1 KG TPU 930

Version: 11 /

Date revised: 23.08.2019

Substance number: 38050057930

Replaces Version: 10 /

Print date: 31.03.20

Type of value	PNEC	
Type	Saltwater	
Concentration	0,01	mg/l
Type of value	PNEC	
Type	Sewage treatment plant (STP)	
Concentration	9,6	mg/l
Type of value	PNEC	
Type	Freshwater sediment	
Concentration	13,7	mg/kg
Type of value	PNEC	
Type	Marine sediment	
Concentration	1,37	mg/kg
Type of value	PNEC	
Type	Soil	
Concentration	2,68	mg/kg

8.2. Exposure controls

Exposure controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

Respiratory protection

If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators. Full mask, filter A

Hand protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

For prolonged or repeated handling nitrile rubber gloves with textile undergloves are required.

Material thickness > 0,5 mm

Breakthrough time < 30 min

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occurred.

Eye protection

Use safety eyewear designed to protect against splash of liquids.

Body protection

Cotton or cotton/synthetic overalls or coveralls are normally suitable.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Form	Pasty
Colour	coloured
Odour	solvent-like



Trade name: Tampa® Pur 1 KG TPU 930

Version: 11 /

Date revised: 23.08.2019

Substance number: 38050057930

Replaces Version: 10 /

Print date: 31.03.20

Odour threshold

Remarks No data available

pH value

Remarks Not applicable

Melting point

Remarks not determined

Freezing point

Remarks not determined

Initial boiling point and boiling range

Value appr. 124 °C

Pressure 1.013 hPa

Source Literature value

Flash point

Value 36 °C

Method ASTM D 6450 (CCCFP)

Evaporation rate (ether = 1) :

Remarks not determined

Flammability (solid, gas)

Not applicable

Upper/lower flammability or explosive limits

Lower explosion limit appr. 0,7 %(V)

Upper explosion limit appr. 10,8 %(V)

Source Literature value

Vapour pressure

Value appr. 7 hPa

Temperature 20 °C

Method calculated

Vapour density

Remarks not determined

DensityValue 1,13 g/cm³

Temperature 20 °C

Method DIN EN ISO 2811

Solubility in water

Remarks partially miscible

Partition coefficient: n-octanol/water

Remarks Not applicable

Ignition temperature

Value appr. 315 °C

Source Literature value

Efflux time

Value > 150 s

Method DIN 53211 4 mm

Explosive properties

evaluation no

Oxidising properties

evaluation None known



Trade name: Tampa® Pur 1 KG TPU 930

Version: 11 /

Date revised: 23.08.2019

Substance number: 38050057930

Replaces Version: 10 /

Print date: 31.03.20

9.2. Other information

Other information

The physical specifications are approximate values and refer to the used safety relevant component(s).

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reactions when stored and handled according to prescribed instructions.

10.2. Chemical stability

Stable under recommended storage and handling conditions (see section 7).

10.3. Possibility of hazardous reactions

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.4. Conditions to avoid

When exposed to high temperatures may produce hazardous decomposition products.

10.5. Incompatible materials

No hazardous reactions when stored and handled according to prescribed instructions.

10.6. Hazardous decomposition products

See chapter 5.2 (Firefighting measures - Special hazards arising from the substance or mixture).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute oral toxicity

Remarks Based on available data, the classification criteria are not met.

Acute dermal toxicity

Remarks Based on available data, the classification criteria are not met.

Acute inhalational toxicity

Remarks Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Remarks Based on available data, the classification criteria are not met.

Serious eye damage/irritation

evaluation corrosive
Remarks The classification criteria are met.

Sensitization

Remarks Based on available data, the classification criteria are not met.

Mutagenicity

Remarks Based on available data, the classification criteria are not met.

Reproductive toxicity

evaluation Suspected of damaging the unborn child.
Remarks The classification criteria are met.

Carcinogenicity

Remarks Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity (STOT)

Single exposure

Remarks The classification criteria are met.
evaluation May cause drowsiness or dizziness.



Trade name: Tampa® Pur 1 KG TPU 930

Version: 11 /

Date revised: 23.08.2019

Substance number: 38050057930

Replaces Version: 10 /

Print date: 31.03.20

Repeated exposure

Remarks Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Experience in practice

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation. Causes serious eye damage. Ingestion may cause nausea, diarrhoea and vomiting. Ingredient butyl glycolate may possibly cause harm to the unborn child if ingested. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Other information

There are no data available on the mixture itself.
The mixture has been assessed following the additivity method of the CLP Regulation (EC) No 1272/2008 and classified for toxicological hazards accordingly.

SECTION 12: Ecological information

12.1. Toxicity

General information

There are no data available on the mixture itself. Do not allow to enter drains or water courses. The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is classified for eco-toxicological properties accordingly. See Sections 2 and 3 for details.

12.2. Persistence and degradability

General information

No data available

12.3. Bioaccumulative potential

General information

There are no data available on the mixture itself.

Partition coefficient: n-octanol/water

Remarks Not applicable

12.4. Mobility in soil

General information

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

General information

There are no data available on the mixture itself.

12.6. Other adverse effects

General information

There are no data available on the mixture itself.

SECTION 13: Disposal considerations



Trade name: Tampa® Pur 1 KG TPU 930

Version: 11 /

Date revised: 23.08.2019

Substance number: 38050057930

Replaces Version: 10 /

Print date: 31.03.20

13.1. Waste treatment methods

Disposal recommendations for the product

Do not allow to enter drains or water courses.

Wastes and emptied containers should be classified in accordance with relevant national regulation.

The European Waste Catalogue classification of this product, when disposed of as waste is

EWC waste code 08 03 12* waste ink containing dangerous substances

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

For further information contact your local waste authority.




Disposal recommendations for packaging

Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers.

Empty containers must be scrapped or reconditioned.

Not emptied containers are hazardous waste (waste code number 150110).

SECTION 14: Transport information

	Land transport ADR/RID	Marine transport IMDG/GGVSee	Air transport ICAO/IATA
Tunnel restriction code	D/E		
14.1. UN number	1263	1263	1263
14.2. UN proper shipping name	PAINT	PAINT	PAINT
14.3. Transport hazard class(es)	3	3	3
Label			
14.4. Packing group	III	III	III
Special provision	640E		
Remarks	The product is viscous; non-dangerous good in Containers with not more than 450 ltrs.	Transport according to 2.3.2.5 of the IMDG Code	
Limited Quantity	5 l		
Transport category	3		
14.5. Environmental hazards	-	no	-

Information for all modes of transport

14.6. Special precautions for user

Transport within the user's premises:

Always transport in closed containers that are upright and secure.



Trade name: Tampa® Pur 1 KG TPU 930

Version: 11 /

Date revised: 23.08.2019

Substance number: 38050057930

Replaces Version: 10 /

Print date: 31.03.20

Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Other information

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

no

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Other information

The product does not contain substances of very high concern (SVHC).

Other information

- All components are contained in the TSCA inventory or exempted.
- All components are contained in the AICS inventory.
- All components are contained in the IECSC inventory.
- All components are contained in the ECL inventory.

15.2. Chemical safety assessment

For this preparation a chemical safety assessment has not been carried out.

SECTION 16: Other information

Hazard statements listed in Chapter 3

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

CLP categories listed in Chapter 3

Acute Tox. 4	Acute toxicity, Category 4
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Dam. 1	Serious eye damage, Category 1
Eye Irrit. 2	Eye irritation, Category 2
Flam. Liq. 2	Flammable liquid, Category 2
Flam. Liq. 3	Flammable liquid, Category 3
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin irritation, Category 2
STOT RE 2	Specific target organ toxicity - repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity - single exposure, Category 3

Supplemental information

Relevant changes compared with the previous version of the safety data sheet are marked with: ***
 This information is based on our present state of knowledge. However, it should not constitute a guarantee for any specific product properties and shall not establish a legally valid relationship.
 The information in this Safety Data Sheet is based on the present state of knowledge and current

Safety data sheet in accordance with regulation (EC) No 1907/2006



Trade name: Tampa® Pur 1 KG TPU 930

Version: 11 /

Date revised: 23.08.2019

Substance number: 38050057930

Replaces Version: 10 /

Print date: 31.03.20

legislation.

It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.

The product should not be used for purposes other than those shown in Section 1 without first referring to the supplier and obtaining written handling instructions.

As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with.

The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation.