

Safety data sheet in accordance with regulation (EC) No 1907/2006

Product Identifier:

Thinner UPPT for Pad Printing

Version: 5 / GB

Date revised: 21.01.2015

Thinner UPPT for Pad Printing

Replaces Version: 4 / GB

Print date: 08.10.15

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/preparation

Screen and pad printing auxiliary

Identified Uses

| | |
|--------|--|
| SU3 | Industrial uses: Uses of substances as such or in preparations at industrial sites |
| SU22 | Professional uses: Public domain (administration, education, entertainment, services, craftsmen) |
| PROC1 | Use in closed process, no likelihood of exposure |
| PROC2 | Use in closed, continuous process with occasional controlled exposure |
| PROC3 | Use in closed batch process (synthesis or formulation) |
| PROC4 | Use in batch and other process (synthesis) where opportunity for exposure arises |
| PROC5 | Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact) |
| PROC8a | Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non dedicated facilities |
| PROC8b | Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities |
| PROC10 | Roller application or brushing |
| PROC11 | Non industrial spraying |
| PROC13 | Treatment of articles by dipping and pouring |
| PROC19 | Hand-mixing with intimate contact and only PPE available |
| ERC4 | Industrial use of processing aids in processes and products, not becoming part of articles |
| ERC8a | Wide dispersive indoor use of processing aids in open systems |
| ERC8d | Wide dispersive outdoor use of processing aids in open systems |

Uses advised against

Consumer uses: Private households (= general public = consumers)

1.3. Details of the supplier of the safety data sheet

ITW Trans Tech
475 North Gary Avenue
Carol Stream, IL 60188
USA

General Information:
ph 630-752-4000
www.itwtranstech.com

352-323-3500

1.4. Emergency telephone number

SECTION 2: Hazards identification ***

2.1. Classification of the substance or mixture

Classification (Regulation (EC) No. 1272/2008)

Classification (Regulation (EC) No. 1272/2008)

| | |
|-------------------|------|
| Flam. Liq. 3 | H226 |
| STOT SE 3 | H335 |
| STOT SE 3 | H336 |
| Asp. Tox. 1 | H304 |
| Aquatic Chronic 2 | H411 |

2.2. Label elements

Labelling according to regulation (EC) No 1272/2008

Hazard pictograms



Signal word

Danger

Hazard statements

| | |
|------|--|
| H226 | Flammable liquid and vapour. |
| H335 | May cause respiratory irritation. |
| H336 | May cause drowsiness or dizziness. |
| H304 | May be fatal if swallowed and enters airways. |
| H411 | Toxic to aquatic life with long lasting effects. |

Precautionary statements ***

| | |
|-----------|--|
| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| P261 | Avoid breathing dust/fume/gas/mist/vapours/spray. |
| P273 | Avoid release to the environment. |
| P301+P310 | IF SWALLOWED: Immediately call a POISON CENTER or doctor. |
| P304+P340 | IF INHALED: Remove person to fresh air and keep comfortable for breathing. |
| P331 | Do NOT induce vomiting. |

Hazardous component(s) to be indicated on label (Regulation (EC) No. 1272/2008)

| | |
|----------|---|
| contains | Solvent naphtha (petroleum), light arom. 1-Methoxy-2-propanol |
|----------|---|

Supplemental information

| | |
|--------|---|
| EUH066 | Repeated exposure may cause skin dryness or cracking. |
|--------|---|

2.3. Other hazards

No special hazards have to be mentioned.

SECTION 3: Composition/information on ingredients ***

3.2. Mixtures

Chemical characterization

Solvent mixture of aromatic hydrocarbons (C9-C10) and glycol ethers

Hazardous ingredients ***

Solvent naphtha (petroleum), light arom.

| | |
|------------|------------|
| CAS No. | 64742-95-6 |
| EINECS no. | 265-199-0 |

Registration no. 01-2119455851-35 (LIST NUMBER 918-668-5)
Concentration >= 50 < 100 %

Classification (Regulation (EC) No. 1272/2008)

| | |
|-------------------|------|
| Flam. Liq. 3 | H226 |
| STOT SE 3 | H336 |
| STOT SE 3 | H335 |
| Asp. Tox. 1 | H304 |
| Aquatic Chronic 2 | H411 |

1-Methoxy-2-propanol

CAS No. 107-98-2
EINECS no. 203-539-1
Registration no. 01-2119457435-35
Concentration >= 10 < 20 %

Classification (Regulation (EC) No. 1272/2008)

| | |
|--------------|------|
| STOT SE 3 | H336 |
| Flam. Liq. 3 | H226 |

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice.

After inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

After skin contact

Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

After eye contact

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Until now no symptoms known so far.

4.3. Indication of any immediate medical attention and special treatment needed

Hints for the physician / treatment

Treat symptomatically

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Recommended: alcohol resistant foam, CO2, powders, water spray/mist, Not be used for safety reasons: water jet

5.2. Special hazards arising from the substance or mixture

In the event of fire the following can be released: Carbon dioxide (CO₂); Carbon monoxide (CO); dense black smoke

5.3. Advice for firefighters

Special protective equipment for fire-fighting

Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Exclude sources of ignition and ventilate the area. Avoid breathing vapours. Refer to protective measures listed in Sections 7 and 8.

6.2. Environmental precautions

Do not allow to enter drains or waterways. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent - avoid use of solvents.

6.4. Reference to other sections

Information regarding Safe handling, see Section 7. Information regarding personal protective measures, see Section 8. Information regarding waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Isolate from sources of heat, sparks and open flame. No sparking tools should be used. Avoid skin and eye contact. Avoid the inhalation of particulates and spray mist arising from the application of this mixture. Smoking, eating and drinking shall be prohibited in application area. For personal protection see Section 8. Never use pressure to empty: container is not a pressure vessel. Always keep in containers of same material as the original one. Comply with the health and safety at work laws. Do not allow to enter drains or water courses.

Advice on protection against fire and explosion

Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

Classification of fires / temperature class / Ignition group / Dust explosion class

| | |
|-------------------------|-----------------------------------|
| Classification of fires | B (Combustible liquid substances) |
| Temperature class | T3 |

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Electrical installations/working materials must comply with the local applied technological safety standards. Storage rooms in which filling operations take place must have a conducting floor. Store in

accordance with national regulation

Hints on storage assembly

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

Further information on storage conditions

Observe label precautions. Store between 15 and 30 °C in a dry, well ventilated place away from sources of heat and direct sunlight. Keep container tightly closed. Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

7.3. Specific end use(s)

Screen and pad printing auxiliary

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limit values

1-Methoxy-2-propanol

| | | | | |
|---|------|-------------------|-----|--------|
| List | EH40 | | | |
| Type | WEL | | | |
| Value | 375 | mg/m ³ | 100 | ppm(V) |
| Short term exposure limit | 560 | mg/m ³ | 150 | ppm(V) |
| Skin resorption / sensibilisation: Sk; Status: 2011 | | | | |

Aromatics

| | | | | |
|-------|------|-------------------|--|--|
| List | EH40 | | | |
| Value | 500 | mg/m ³ | | |

Mesitylene

| | | | | |
|--------------|------|-------------------|----|--------|
| List | EH40 | | | |
| Type | WEL | | | |
| Value | 125 | mg/m ³ | 25 | ppm(V) |
| Status: 2011 | | | | |

1,2,4-Trimethylbenzene

| | | | | |
|--------------|------|-------------------|----|--------|
| List | EH40 | | | |
| Type | WEL | | | |
| Value | 125 | mg/m ³ | 25 | ppm(V) |
| Status: 2011 | | | | |

Isopropylbenzene

| | | | | |
|---|------|-------------------|----|--------|
| List | EH40 | | | |
| Type | WEL | | | |
| Value | 125 | mg/m ³ | 25 | ppm(V) |
| Short term exposure limit | 250 | mg/m ³ | 50 | ppm(V) |
| Skin resorption / sensibilisation: Sk; Status: 2011 | | | | |

Derived No/Minimal Effect Levels (DNEL/DMEL)

Solvent naphtha (petroleum), light arom.

| | | | | |
|----------------------|--------------------------------|--|--|-------|
| Type of value | Derived No Effect Level (DNEL) | | | |
| Reference group | Consumer | | | |
| Duration of exposure | Long term | | | |
| Route of exposure | oral | | | |
| Mode of action | Systemic effects | | | |
| Concentration | 11 | | | mg/kg |

| | | | | |
|----------------------|--------------------------------|--|--|--|
| Type of value | Derived No Effect Level (DNEL) | | | |
| Reference group | Consumer | | | |
| Duration of exposure | Long term | | | |

| | | |
|-------------------|------------------|-------|
| Route of exposure | dermal | |
| Mode of action | Systemic effects | |
| Concentration | 11 | mg/kg |

| | | |
|----------------------|--------------------------------|-------------------|
| Type of value | Derived No Effect Level (DNEL) | |
| Reference group | Consumer | |
| Duration of exposure | Long term | |
| Route of exposure | inhalative | |
| Mode of action | Systemic effects | |
| Concentration | 32 | mg/m ³ |

| | | |
|----------------------|--------------------------------|-------------------|
| Type of value | Derived No Effect Level (DNEL) | |
| Reference group | Worker | |
| Duration of exposure | Long term | |
| Route of exposure | inhalative | |
| Mode of action | Systemic effects | |
| Concentration | 150 | mg/m ³ |

1-Methoxy-2-propanol

| | | |
|----------------------|--------------------------------|-------------------|
| Type of value | Derived No Effect Level (DNEL) | |
| Reference group | Worker | |
| Duration of exposure | Acute | |
| Route of exposure | inhalative | |
| Mode of action | Local effects | |
| Concentration | 553,5 | mg/m ³ |

| | | |
|----------------------|--------------------------------|-----------------|
| Type of value | Derived No Effect Level (DNEL) | |
| Reference group | Worker | |
| Duration of exposure | Long term | |
| Route of exposure | dermal | |
| Mode of action | Systemic effects | |
| Concentration | 50,6 | mg/person/ d |

| | | |
|----------------------|--------------------------------|-------------------|
| Type of value | Derived No Effect Level (DNEL) | |
| Reference group | Worker | |
| Duration of exposure | Long term | |
| Route of exposure | inhalative | |
| Mode of action | Systemic effects | |
| Concentration | 369 | mg/m ³ |

| | | |
|----------------------|--------------------------------|-------|
| Type of value | Derived No Effect Level (DNEL) | |
| Reference group | General Population | |
| Duration of exposure | Long term | |
| Route of exposure | dermal | |
| Mode of action | Systemic effects | |
| Concentration | 18,1 | mg/kg |

| | | |
|----------------------|--------------------------------|-------------------|
| Type of value | Derived No Effect Level (DNEL) | |
| Reference group | General Population | |
| Duration of exposure | Long term | |
| Route of exposure | inhalative | |
| Mode of action | Systemic effects | |
| Concentration | 43,9 | mg/m ³ |

| | | |
|---------------|--------------------------------|--|
| Type of value | Derived No Effect Level (DNEL) | |
|---------------|--------------------------------|--|

| | | |
|----------------------|--------------------|---------|
| Reference group | General Population | |
| Duration of exposure | Long term | |
| Route of exposure | oral | |
| Mode of action | Systemic effects | |
| Concentration | 3,3 | mg/kg/d |

Predicted No Effect Concentration (PNEC)

1-Methoxy-2-propanol

| | | |
|---------------|------------------------------|-------|
| Type of value | PNEC | |
| Type | Freshwater | |
| Concentration | 10 | mg/l |
| Type of value | PNEC | |
| Type | Water | |
| Concentration | 41,6 | mg/kg |
| Type of value | PNEC | |
| Type | Sediment | |
| Concentration | 41,6 | mg/kg |
| Type of value | PNEC | |
| Type | Marine sediment | |
| Concentration | 4,17 | mg/kg |
| Type of value | PNEC | |
| Type | Soil | |
| Concentration | 2,47 | mg/kg |
| Type of value | PNEC | |
| Type | Sewage treatment plant (STP) | |
| Concentration | 100 | mg/l |

8.2. Exposure controls

Exposure controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

Respiratory protection

If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators. Full mask, filter A

Hand protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

For prolonged or repeated handling nitrile rubber gloves with textile undergloves are required.

Material thickness > 0,5 mm

Breakthrough time < 30 min

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin, they should however not be applied

once exposure has occurred.

Eye protection

Use safety eyewear designed to protect against splash of liquids.

Body protection

Cotton or cotton/synthetic overalls or coveralls are normally suitable.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

| | | | |
|---|---------------------|-----|-------------------|
| Form | Liquid | | |
| Colour | colourless, clear | | |
| Odour | solvent-like | | |
| Odour threshold | | | |
| Remarks | No data available | | |
| pH value | | | |
| Remarks | Not applicable | | |
| Melting point | | | |
| Remarks | not determined | | |
| Freezing point | | | |
| Remarks | not determined | | |
| Initial boiling point and boiling range | | | |
| Value | appr. 120 | | °C |
| Pressure | 1.013 | hPa | |
| Source | Literature value | | |
| Flash point | | | |
| Value | 33 | | °C |
| Method | ASTM D 6450 (CCCFP) | | |
| Evaporation rate (ether = 1) : | | | |
| Remarks | not determined | | |
| Flammability (solid, gas) | | | |
| Not applicable | | | |
| Upper/lower flammability or explosive limits | | | |
| Lower explosion limit | appr. 0,7 | | %(V) |
| Upper explosion limit | appr. 13,7 | | %(V) |
| Source | Literature value | | |
| Vapour pressure | | | |
| Value | appr. 5 | | hPa |
| Temperature | 20 | °C | |
| Method | calculated | | |
| Vapour density | | | |
| Remarks | not determined | | |
| Density | | | |
| Value | 0,880 | | g/cm ³ |
| Temperature | 20 | °C | |
| Method | DIN EN ISO 2811 | | |
| Solubility in water | | | |
| Remarks | partially miscible | | |
| Partition coefficient: n-octanol/water | | | |

| | | | |
|-----------------------------|------------------|----|----|
| Remarks | Not applicable | | |
| Ignition temperature | | | |
| Value | appr. 287 | | °C |
| Source | Literature value | | |
| Efflux time | | | |
| Value | < 12 | | s |
| Temperature | 20 | °C | |
| Method | DIN 53211 4 mm | | |
| Explosive properties | | | |
| evaluation | no | | |
| Oxidising properties | | | |
| evaluation | None known | | |

9.2. Other information**Other information**

The physical specifications are approximate values and refer to the used safety relevant component(s).

SECTION 10: Stability and reactivity**10.1. Reactivity**

No hazardous reactions when stored and handled according to prescribed instructions.

10.2. Chemical stability

Stable under recommended storage and handling conditions (see section 7).

10.3. Possibility of hazardous reactions

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.4. Conditions to avoid

When exposed to high temperatures may produce hazardous decomposition products.

10.5. Incompatible materials

No hazardous reactions when stored and handled according to prescribed instructions.

10.6. Hazardous decomposition products

See chapter 5.2 (Firefighting measures - Special hazards arising from the substance or mixture).

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute oral toxicity (Components)****1-Methoxy-2-propanol**

| | | | |
|---------|------|--|-------|
| Species | rat | | |
| LD50 | 5200 | | mg/kg |

Acute dermal toxicity (Components)**1-Methoxy-2-propanol**

| | | | |
|---------|--------|--|-------|
| Species | rabbit | | |
| LD50 | 14000 | | mg/kg |

Experience in practice

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache,

dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage. Ingestion may cause nausea, diarrhoea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Other information

There are no data available on the mixture itself.

The mixture has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and classified for toxicological hazards accordingly.

SECTION 12: Ecological information

12.1. Toxicity

General information

There are no data available on the mixture itself. Do not allow to enter drains or water courses. The mixture has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and is classified for eco-toxicological properties accordingly. See Sections 2 and 3 for details.

Fish toxicity (Components)

Solvent naphtha (petroleum), light arom.

| | | | | |
|----------------------|--|---|--|------|
| Species | rainbow trout (<i>Oncorhynchus mykiss</i>) | | | |
| | 9,2 | | | mg/l |
| Duration of exposure | 96 | h | | |

1-Methoxy-2-propanol

| | | | | |
|----------------------|---------------------------------------|------|--|------|
| Species | golden orfe (<i>Leuciscus idus</i>) | | | |
| LC0 | > | 4600 | | mg/l |
| Duration of exposure | 96 | h | | |

Daphnia toxicity (Components)

Solvent naphtha (petroleum), light arom.

| | | | | |
|----------------------|-----|---|--|------|
| | 3,2 | | | mg/l |
| Duration of exposure | 48 | h | | |

1-Methoxy-2-propanol

| | | | | |
|----------------------|---------------|-------|--|------|
| Species | Daphnia magna | | | |
| EC50 | | 23300 | | mg/l |
| Duration of exposure | 48 | h | | |

Algae toxicity (Components)

Solvent naphtha (petroleum), light arom.

| | | | | |
|----------------------|-------------|----|-----|------|
| Species | Desmodesmus | | | |
| | 2,6 | to | 2,9 | mg/l |
| Duration of exposure | 72 | h | | |

1-Methoxy-2-propanol

| | | | | |
|----------------------|-------------|------|--|------|
| Species | Desmodesmus | | | |
| EC50 | > | 1000 | | mg/l |
| Duration of exposure | 168 | h | | |

Bacteria toxicity (Components)

1-Methoxy-2-propanol

| | | | | |
|---------|------------------|------|--|------|
| Species | activated sludge | | | |
| EC50 | > | 1000 | | mg/l |

12.2. Persistence and degradability

General information

No data available

Biodegradability (Components)

1-Methoxy-2-propanol

| | | |
|-----------------------------|---|---|
| Value | 90 | % |
| Duration of test evaluation | 28 | d |
| Method | Readily biodegradable (according to OECD criteria) OECD 301 F | |

12.3. Bioaccumulative potential

General information

There are no data available on the mixture itself.

Partition coefficient: n-octanol/water

| | |
|---------|----------------|
| Remarks | Not applicable |
|---------|----------------|

12.4. Mobility in soil

General information

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

General information

There are no data available on the mixture itself.

12.6. Other adverse effects

General information

There are no data available on the mixture itself.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations for the product

Do not allow to enter drains or water courses.

Wastes and emptied containers should be classified in accordance with relevant national regulation.

The European Waste Catalogue classification of this product, when disposed of as waste is

EWC waste code 08 03 12* waste ink containing dangerous substances

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

For further information contact your local waste authority.

Disposal recommendations for packaging

Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers.

Empty containers must be scrapped or reconditioned.

Not emptied containers are hazardous waste (waste code number 150110).

SECTION 14: Transport information

Land transport ADR/RID

14.1. UN number

UN 1263

14.2. UN proper shipping name

PAINT RELATED MATERIAL (Solvent naphtha (petroleum), light arom.)

14.3. Transport hazard class(es)

Class 3
 Label 3
14.4. Packing group
 Packing group III
 Special provision 640E
 Limited Quantity 5 I
 Transport category 4

14.5. Environmental hazards
 ENVIRONMENTALLY HAZARDOUS
 Tunnel restriction code D/E

Marine transport IMDG/GGVSee

14.1. UN number
 UN 1263
14.2. UN proper shipping name
 PAINT RELATED MATERIAL (Solvent naphtha (petroleum), light arom.)
14.3. Transport hazard class(es)
 Class 3
14.4. Packing group
 Packing group III
14.5. Environmental hazards
 Marine Pollutant

Air transport ICAO/IATA

14.1. UN number
 UN 1263
14.2. UN proper shipping name
 PAINT RELATED MATERIAL (Solvent naphtha (petroleum), light arom.)
14.3. Transport hazard class(es)
 Class 3
14.4. Packing group
 Packing group III
14.5. Environmental hazards
 ENVIRONMENTALLY HAZARDOUS

Information for all modes of transport

14.6. Special precautions for user
 Transport within the user's premises:
 Always transport in closed containers that are upright and secure.
 Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Other information

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code
 no

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Major-accident categories acc. 96/82/EC

| | | | | | | |
|----------|------|---------------------------|-----------|----|------------|----|
| Category | 9.II | Dangerous for environment | 200.000 | kg | 500.000 | kg |
| Category | 6 | Flammable | 5.000.000 | kg | 50.000.000 | kg |

VOC

| | | | | |
|----------|-----|---|-----|-----|
| VOC (EU) | 100 | % | 880 | g/l |
|----------|-----|---|-----|-----|

Other information

The product does not contain substances of very high concern (SVHC).

Other information

All components are contained in the TSCA inventory or exempted.
All components are contained in the AICS inventory.
All components are contained in the PICCS inventory.
All components are contained in the DSL inventory.
All components are contained in the IECSC inventory.
All components are contained in the NZIOC inventory.
All components are contained in the ENCS inventory.
All components are contained in the ECL inventory.

15.2. Chemical safety assessment

For this preparation a chemical safety assessment has not been carried out.

SECTION 16: Other information

Hazard statements listed in Chapter 3

| | |
|------|--|
| H226 | Flammable liquid and vapour. |
| H304 | May be fatal if swallowed and enters airways. |
| H335 | May cause respiratory irritation. |
| H336 | May cause drowsiness or dizziness. |
| H411 | Toxic to aquatic life with long lasting effects. |

CLP categories listed in Chapter 3

| | |
|-------------------|--|
| Aquatic Chronic 2 | Hazardous to the aquatic environment, chronic, Category 2 |
| Asp. Tox. 1 | Aspiration hazard, Category 1 |
| Flam. Liq. 3 | Flammable liquid, Category 3 |
| STOT SE 3 | Specific target organ toxicity - single exposure, Category 3 |

Supplemental information

Relevant changes compared with the previous version of the safety data sheet are marked with: ***

This information is based on our present state of knowledge. However, it should not constitute a guarantee for any specific product properties and shall not establish a legally valid relationship.

The information in this Safety Data Sheet is based on the present state of knowledge and current legislation.

It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.

The product should not be used for purposes other than those shown in Section 1 without first referring to the supplier and obtaining written handling instructions.

As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with.

The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation.

Trusted Partner for Your Product Decorating Needs

Trans Tech 475 North Gary Avenue, Carol Stream, IL 60188
Tel +1 (630) 752 4000 Fax +1 (630) 752 4467
Email sales@itwtranstech.com

www.itwtranstech.com www.itwids.com

A MEMBER OF

 **IDS** | A Division of ITW