according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) No 453/2010



Article no.: 38571

 Date of print:
 18.03.2014
 Revision date: 18.03.2014
 EN

 Version:
 3.0
 Date of issue: 17.03.2014
 Page:1 / 8

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifiers:

Article no. (manufacturer / supplier): Thinner 38571

Identification of the substance or preparation:

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:

Printing aids

1.3. Manufacturer / Distributor | TW Trans Tech

475 North Gary Avenue Carol Stream, IL 60188 USA

+1 (630) 752 4000 www.itwtranstech.com

1.4. Emergency telephone

number

+1 (352) 323 3500 (Info Trac)

#### **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

## Classification according to EC regulation 1272/2008 (CLP):

This mixture is classified as hazardous according to regulation (EC) No. 1272/2008 [CLP].

Flam. Liq. 3 / H226 flammable liquids Flammable liquid and vapour. Skin Irrit. 2 / H315 skin corrosion/irritation Causes skin irritation.

Eye Dam. 1 / H318 Serious eye damage/eye irritation Causes serious eye damage.

STOT SE 3 / H336 Specific target organ toxicity (single May cause drowsiness or dizziness.

exposure)

## Classification according to Directive 67/548/EEC or 1999/45/EC

The preparation is dangerous in the sense of Directive 1999/45/EC.

R10 Flammable

Xi; R38-41 Irritant Irritating to skin. Risk of serious damage to

eyes.

R67 Vapours may cause drowsiness and dizziness.

#### 2.2. Label elements

# Labelling (CLP)

## **Hazard pictograms**







Danger

#### **Hazard statements:**

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H318 Causes serious eye damage. H336 May cause drowsiness or dizziness.

Safety precautions:

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical equipment.

P242 Use only non-sparking tools.

# according to Regulation (EC) No. 1907/2006 (REACH)

according to Regulation (EU) No 453/2010

Article no.: 38571

Date of print: 18.03.2014 Revision date: 18.03.2014 EN Version: 3.0 Date of issue: 17.03.2014 Page: 2 / 8

P243 Take precautionary measures against static discharge.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash hands thoroughly after handling.
Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P303 + P361 + P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER or doctor/ physician.
P312 Call a POISON CENTER or doctor/physician if you feel unwell.

P332 + P313 If skin irritation occurs: Get medical advice/attention.
P362 Take off contaminated clothing and wash it before reuse.
P370 + P378 In case of fire: Use Extinguishing powder or sand for extinction.
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Keep locked up.

P501 Dispose of contents/container to industrial incineration plant.

contains:

cyclohexanone

2-ethoxy-1-methylethyl acetate

#### Supplemental Hazard information (EU):

n.a.

#### Labelling (67/548/EEC or 1999/45/EC)



Xi Irritant

#### **Hazard statements:**

10 Flammable38 Irritating to skin.

41 Risk of serious damage to eyes.

Vapours may cause drowsiness and dizziness.

Safety precautions:

26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Wear eye/face protection.

51 Use only in well-ventilated areas.

contains:

cyclohexanone

#### Special provisions concerning the labelling of certain mixtures

n.a.

#### 2.3. Other hazards

## **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

chemical characterization (preparation)

**Description:** Organic solvent or solvent mixture

Hazardous ingredients:

Classification according to EC regulation 1272/2008 (CLP):

EC No:	REACH No:	
CAS No.:	Chemical name:	% by weight
INDEX no.:	classification:	Remark:
259-370-9		50 - 100
54839-24-6	2-ethoxy-1-methylethyl acetate	
603-177-00-8	Flam. Liq. 3 H226 / STOT SE 3 H336	
203-631-1	01-2119453616-35-XXXX	20 - 25
108-94-1	cyclohexanone	

# according to Regulation (EC) No. 1907/2006 (REACH)

according to Regulation (EU) No 453/2010

Article no.: 38571

 Date of print:
 18.03.2014
 Revision date: 18.03.2014
 EN

 Version:
 3.0
 Date of issue: 17.03.2014
 Page: 3 / 8

606-010-00-7 Flam. Lig. 3 H226 / Acute Tox. 4 H302 / Acute Tox. 4 H312 / Acute Tox. 4

H332 / Skin Irrit. 2 H315 / Eye Dam. 1 H318

203-603-9 01-2119475791-29-XXXX 15 - 20

108-65-6 2-methoxy-1-methylethyl acetate

607-195-00-7 Flam. Liq. 3 H226

#### Classification according to Directive 67/548/EEC or 1999/45/EC

EC No:	REACH No:	
CAS No.:	Identification of the hazard:	% by weight
INDEX no.:	classification:	Remark:
259-370-9		50 - 100
54839-24-6	2-ethoxy-1-methylethyl acetate	
603-177-00-8	R10 / R67	
203-631-1	01-2119453616-35-XXXX	20 - 25
108-94-1	cyclohexanone	
606-010-00-7	R10 / Xn; R20/21/22 / Xi; R38-41	
203-603-9	01-2119475791-29-XXXX	15 - 20
108-65-6	2-methoxy-1-methylethyl acetate	*
607-195-00-7	R10	

#### **Additional information**

Full text of R-phrases: see section 16. Full text of H-phrases: see section 16.

## **SECTION 4: First aid measures**

#### .1. Description of first aid measures:

#### **General information:**

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

#### After inhalation

Move victim to fresh air. Put victim at rest and keep warm. In case of irregular breathing or respiratory arrest provide artificial respiration.

## In case of skin contact:

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

## In case of eye contact:

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice.

#### After ingestion:

If swallowed, rinse mouth with water (only if the person is conscious). Consult physician immediately. Keep victim calm. Do not induce vomiting.

### 4.2. Most important symptoms and effects, both acute and delayed:

In all cases of doubt, or when symptoms persist, seek medical advice.

#### 4.3. Indication of any immediate medical attention and special treatment needed

#### **SECTION 5: Firefighting measures**

## 5.1. Extinguishing media

#### Suitable extinguishing media:

Alcohol resistant foam, Carbon dioxide, Powder, spray mist, (water)

#### Extinguishing media which must not be used for safety reasons:

Strong water jet

#### 5.2. Special hazards arising from the substance or mixture

Inhaling hazardous decomposing products can cause serious health damage.

#### 5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways. Treat runoff as hazardous.

<sup>\*</sup> Substance with a common (EC) occupational exposure limit value.

## according to Regulation (EC) No. 1907/2006 (REACH)

according to Regulation (EU) No 453/2010

Article no.: 38571

Date of print: 18.03.2014 Revision date: 18.03.2014 EN Version: 3.0 Date of issue: 17.03.2014 Page: 4 / 8

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

#### 6.2. Environmental measures

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

#### 6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see chapter 13). Clean using cleansing agents. Do not use solvents.

#### 6.4. Reference to other sections

Observe protective provisions (see chapter 7 and 8).

### **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

#### Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. When using do not eat, drink or smoke. Personal protection equipment: refer to chapter 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

#### Precautions against fire and explosion:

Vapours are heavier than air and will spread at floor level. Vapours form explosive mixtures with air.

#### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storerooms and containers:

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

#### Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

#### Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 5 °C and 35 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

## 7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

## **SECTION 8: Exposure controls/personal protection**

## 8.1. Control parameters

EC No: CAS No.:	Description:	type: Country:	Limi	it value WA (EC)	
203-631-1	cyclohexanone	-	408	102	mg/m3
108-94-1	•	EN	100	25	ppm
203-603-9	2-methoxy-1-methylethyl acetate		550	275	mg/m3
108-65-6		EG	100	50	ppm

#### **Additional information**

TWA (EC): Occupational exposure limit value

STEL (EC): Short-term occupational exposure limit value

#### 8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and

# according to Regulation (EC) No. 1907/2006 (REACH)

according to Regulation (EU) No 453/2010

Article no.: 38571

Date of print: 18.03.2014 Revision date: 18.03.2014 EN Version: 3.0 Date of issue: 17.03.2014 Page: 5 / 8

solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

#### Occupational exposure controls:

#### Respiratory protection:

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Use only respiratory protection equipment with CE-symbol including four digit test number.

#### Hand protection:

For prolonged or repeated handling the following glove material must be used: butyl rubber

Thickness of the glove material: > 0,4 mm; Penetration time (maximum wearing period): > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles: DIN EN 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

#### Eye protection:

Wear closely fitting protective glasses in case of splashes.

#### **Body protection:**

Recommendation: Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

#### Protective measures:

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

#### **Environmental exposure controls**

Do not allow to enter into surface water or drains, refer to chapter 7. No further action is necessary.

#### **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Appearance:

Physical state: liquid
Colour as labeled
Odour: typical

Safety relevant basis data	ι	Jnit	Method	Remark:
Flash point:	43 °	C.	DIN 53213	
Ignition temperature (AIT):	315 °	°C		
lower explosion limit:	1,0 ∖	√ol-%		
Upper explosion limit:	10,8 V	√ol-%		
Vapour pressure at 20 °C:	5,00 n	mbar		
Density at 20 °C:	0,95 g	g/cm³		
Water solubility (g/l):	partial soluble			
pH at 20 °C:	-			
Viscosity at 20 °C	11 s 4 mm		DIN 53211	
Solvent separation test (%):	< 3 %	%	ADR/RID	
Solid content (%):	0,00 %	% by weight		
solvent content:				
Organic solvents:	100 %	by weight		
Water:	0 %	by weight		

#### 9.2. Other information:

## **SECTION 10: Stability and reactivity**

## 10.1. Reactivity

## 10.2. Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to chapter 7.

## 10.3. Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

#### 10.4. Conditions to avoid

Hazardous decomposition byproducts may form with exposure to high temperatures.

#### 10.5. Incompatible materials

#### 10.6. Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide,

# according to Regulation (EC) No. 1907/2006 (REACH)

according to Regulation (EU) No 453/2010

Article no.: 38571

Revision date: 18.03.2014 Date of print: 18.03.2014 Page:6 / 8 Version: Date of issue: 17.03.2014

smoke, nitrogen oxides.

#### **SECTION 11: Toxicological information**

No data on preparation itself available.

## 11.1. Information on toxicological effects

#### **Acute toxicity**

Toxicological data are not available.

#### Irritant and corrosive effects

Toxicological data are not available.

#### Sensitisation

Toxicological data are not available.

#### Specific target organ toxicity

Toxicological data are not available.

#### **Aspiration hazard:**

Toxicological data are not available.

#### Practical experience

Other observations:

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

#### **Overall Assessment on CMR properties:**

The components in this formulation do not meet the criteria for classification as CMR category 1 or 2.

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and classified according to the toxicological dangers. See chapters 2 and 15 for details.

#### **SECTION 12: Ecological information**

#### Overall evaluation:

There is no information available on the preparation itself.

Do not allow to enter into surface water or drains.

#### 12.1. Toxicity

Toxicological data are not available.

#### 12.2. Persistence and degradability

Toxicological data are not available.

#### 12.3. Bioaccumulative potential

Toxicological data are not available.

#### 12.4. Mobility in soil

Toxicological data are not available.

#### 12.5. Results of PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

#### 12.6. Other adverse effects

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and is not classified as dangerous for the environment.

## **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

#### Appropriate disposal / Product

#### Recommendation:

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to EC directives 75/442/EEC and 91/689/EEC in the corresponding versions, covering waste and dangerous waste.

## according to Regulation (EC) No. 1907/2006 (REACH)

according to Regulation (EU) No 453/2010

Article no.: 38571

 Date of print:
 18.03.2014
 Revision date: 18.03.2014
 EN

 Version:
 3.0
 Date of issue: 17.03.2014
 Page: 7 / 8

#### Control report for waste code/ waste marking according to EAKV:

140603 other solvents and solvent mixtures

Contaminated packaging:

Recommendation:

Cleaned containers may be recycled. Vessels not properly emptied are special waste.

### **SECTION 14: Transport information**

14.1. **UN-No.:** 

1263

14.2. UN proper shipping name

Land transport (ADR/RID):

Sea transport (IMDG):

Air transport (ICAO-TI / IATA-DGR):

Paint related material

PAINT RELATED MATERIAL

Paint related material

14.3. Transport hazard class(es)

3

14.4. Packing Group:

Ш

14.5. Environmental hazards:

Land transport (ADR/RID) n.a.

Marine pollutant: n.a.

14.6. Environmental hazards

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

Further remarks:

Land transport (ADR/RID)

Tunnel restriction code: D/E

Sea transport (IMDG)

EmS-No.: F-E, S-E

14.7. Special precautions for user

not applicable

#### **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**EU** legislation

Information according to 1999/13/EC about limitation of emissions of volatile organic compounds (VOC-guideline).

 VOC-value (in g/l) ISO 11890-2:
 947,600

 VOC-value (in g/l) ASTM D 2369:
 947,600

**National regulations** 

Informations on working limitations:

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this preparation were not carried out.

## **SECTION 16: Other information**

#### Relevant R-and H-phrases (Number and full text):

Flam. Liq. 3 / H226 flammable liquids Flammable liquid and vapour.

STOT SE 3 / H336 Specific target organ toxicity (single May cause drowsiness or dizziness.

exposure)

Acute Tox. 4 / H302 Acute toxicity (oral) Harmful if swallowed.

Acute Tox. 4 / H312 Acute toxicity (dermal) Harmful in contact with skin.

Acute Tox. 4 / H332 Acute toxicity (inhalative) Harmful if inhaled.

# according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) No 453/2010

Article no.: 38571

Date of print: 18.03.2014 Revision date: 18.03.2014 EN Version: 3.0 Date of issue: 17.03.2014 Page: 8 / 8

Skin Irrit. 2 / H315 skin corrosion/irritation Causes skin irritation.

Eye Dam. 1 / H318 Serious eye damage/eye irritation Causes serious eye damage.

R10 Flammable

Xn; R20/21/22 Harmful Harmful by inhalation, in contact with skin and if

swallowed.

Xi; R38-41 Irritant Irritating to skin. Risk of serious damage to

eyes.

R67 Vapours may cause drowsiness and dizziness.

#### Further remarks:

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in chapter 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.

#### Remarks:

n.a. = not applicable